

## CCT Selectable Bath Light

Wall Mounted • Damp Location Listed PROGRESS LED



### Description:

This linear LED light fixture features a crisp opal white shade shaped into a tubular design with a seamless aesthetic. The fixture includes a 24w integrated LED. The color temperature is color selectable for 3000K, 4000K or 5000K.

### Specifications:

- Features a crisp opal white PMMA diffuser into a tubular design with a seamless aesthetic.
- CCT selectable (3000K, 4000K, 5000K). Internal switch allows color selection.
- 90 CRI.\*
- 2124 delivered lumens.
- Perfect for any modern, luxury, or transitional settings.
- Measures 26-3/8-inch width by 6-1/8-inch height.
- 24w integrated LED
- Includes installation instructions and mounting hardware.
- Progress Lighting products are designed for exceptional quality, reliability, and functionality.
- \*Performance values based on test data of 3000K. Performance values will be higher for 4000K and 5000K selection.
- Dimmable to 10% brightness (See Dimming Notes)
- Mounting backplate for outlet box included
- 6 in of wire supplied

### Performance:

|                        |                                     |
|------------------------|-------------------------------------|
| Input Power            | 24 W                                |
| Input Voltage          | 120 V                               |
| Input Frequency        | 60 Hz                               |
| Lumens/LPW (Delivered) | 2,124/87.8 (LM-79)*                 |
| CCT                    | 3000, 4000, 5000 K                  |
| CRI                    | 90 CRI                              |
| Life (hours)           | 50000 (L70/TM-21)                   |
| EMI/RFI                | Meets FCC Title 47, Part 15 Class B |
| Warranty               | 5-year Limited Warranty             |
| Labels                 | cETLus Damp Location Listed         |
|                        | ENERGY STAR® qualified              |
|                        | Meets California Title 24 JA8-2016  |

\*Performance values based on test data of 3000K. Performance values will be higher for 4000K and 5000K selection

# P300239-060-CS



### Dimensions:

Width: 26-3/8 in  
 Height: 6-1/8 in  
 Depth: 4-5/8 in

White PMMA diffuser  
 Width: 26-3/8 in  
 Height: 4-5/8 in

**Dimming Notes:**

---

P300239-060-CS is designed to be compatible with many Triac/ELV controls.

The following is a partial list of known compatible dimmer controls.

**Dimming Controls:**

---

IDevices IDEV009

Leviton 6672

Lutron DVELV-300P

Lutron DVCL-253P

Lutron Caseta Wireless

Lutron AYCL-153P

Lutron SCL-153P

Lutron TGCL-153-PH-WH

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.

**P300239-060-CS**