

One-Light Outdoor

Wall mounted • Wet location listed PROGRESS LED



Description:

Endorse celebrates the traditional form of a gas-powered coach light with illumination from an LED source. A die-cast aluminum, powdered coated frame created an intriguing visual effect with the clear beveled glass. An optional fluted glass column is offered as an accessory (P8774-31). 3000K, 90+ CRI, 623 lumens (source).

Specifications:

- Black (-31) (powder coat paint)
- Die-cast aluminum Construction
- Clear glass beveled panels (top), Clear glass beveled panels (bottom)
- LED Module is replaceable (part # 93054049)
- Clear beveled glass panels.
- Traditional form.
- Intriguing visual effect.
- 623 lumens 69.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR® qualified
- Meets California Title 24 high efficacy requirements for outdoor use only

Performance:

| | |
|---------------------|--|
| Number of Modules | 1 |
| Input Power | 9w |
| Input Voltage | 120 V |
| Input Frequency | 60 Hz |
| Lumens/LPW (Source) | 623/69.2 (LM-82) |
| CCT | 3000 K |
| CRI | 90 CRI |
| Life (hours) | 60,000 (L70/TM-21) |
| FCC | Meets FCC Title 47, Part 15 Class B |
| Min. Start Temp | -30 °C |
| Max. Operating Temp | 30 °C |
| Warranty | 5 year warranty |
| Labels | cCSAus Wet location listed ENERGY STAR® qualified Meets California Title 24 high efficacy requirements for outdoor use only |

P6056-3130K9

Images:



Dimensions:

Width: 6-3/4"
Depth: 7-5/8"
Height: 12"
H/CTR: 3-1/4"

Glass
Width: 0-3/16"
Length: 4-9/16"
Height: 2-9/16"
Glass 2
Width: 0-3/16"
Length: 5-5/16"
Height: 5-7/8"

P6056-3130K9

Dimming Notes:

P6056 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron Nova T NTELV-300

Lutron Vieri VTELV-600

Lutron Ariadni AYCL-153P

Lutron Diva DVCL-153P

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.