

Fairway LED

Ceiling Flush Mounted • Wet Location Listed **PROGRESS LED**

Description:

Fairway Collection 7 in. White LED Surface Mount Light

Specifications:

- Diffused Polycarbonate Lens
- Dimmable to 10% brightness (See Dimming Notes)
- Housing covers a standard 4" recessed outlet box

Performance:

Input Power	11 W
Input Voltage	120 VAC
Input Frequency	60 Hz
Lumens/LPW (Delivered)	857/82 (LM-79)
CRI	90 CRI
Life (hours)	50000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Warranty	5-year Limited Warranty
Labels	cCSAus Wet Location Listed
	Meets California Title 24 JA8-2019

P810042-028-30



Dimensions:

Diameter: 7 in
Height: 1-1/8 in



Photometrics:

ELECTRICAL DATA	P810042-028-30
Input Voltage	120 VAC
Input Frequency	60 Hz
THD	<20%
EMI/RFI	FCC Title 47, Part 15, Class B
Operating Temperature	-25 °C to 50
Dimming	Yes*
Over-voltage, over-current, short-circuit protected	

*See Dimming Notes for more information

P810042-028-30

P810042-028-30

Dimming Notes:

P810042-028-30 is designed to be compatible with many Triac/ELV controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

- Lutron NTELV-300
- Lutron DVELV-300P
- Lutron DVCL-253P
- Lutron Caséta
- Leviton 6672
- Leviton 6674
- Lutron AYCL-153P
- Lutron SCL-153P
- Lutron TGCL-153PH
- Lutron MACL-153M
- Eaton - AAL06
- Eaton - SAL06P

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements. Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.