

LED Mini-Pendant

 Ceiling cord mounted • Dry location listed **PROGRESS LED**


P5072-2030K9

Description:

A modern LED pendant featuring contrasting textures using a sandblasted glass inside accented by a polished outside surface. Enjoy a glowing effect as a result of the shades internal refraction. Antique Bronze finish.

Specifications:

- Antique Bronze (-20) (painted)
- Steel Construction
- Clear Outside Sandblast Inside glass shade
- LED Module is replaceable (part # 93054049)
- A modern LED pendant.
- Features contrasting textures.
- Creates a glowing effect.
- 623 lumens 69.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 10 feet of wire supplied
- ENERGY STAR® qualified

Performance:

Number of Modules	1
Input Power	9w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	623/69.2 (LM-82)
Lumens/LPW (Delivered)	534/67.6 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	60,000 (L70/TM-21)
FCC	Meets FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Dry location listed ENERGY STAR® qualified

Images:



Dimensions:

Diameter: 9"
Height: 4-3/4"
Overall Ht. W/Cord: 125"

Glass
Width: 9"
Length: 9"
Height: 0-7/8"

P5072-2030K9**Dimming Notes:**

P5072 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron Nova T NTELV-300

Lutron Vieri VTELV-600

Lutron Ariadni AYCL-153P

Lutron Diva DVCL-153P

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.